

# Two-Toning with K-UTG

K-UTG Tape →



Other Tapes

#48060 3/4" x 55 yd

#48063 1/4" x 55 yd

Will not bleed!

**K-UTG Gold Tape** *With acrylic adhesive for masking on difficult surfaces and color separation (two-toning).* Extremely thin, flexible, semi-translucent and UV-resistant. Tape can be lifted and repositioned without leaving any residue.

## Two-Toning with Onyx Waterborne Basecoat

1. Start with a properly cleaned and prepped panel.
2. If using a sealer, allow it to flash completely under ventilation for the prescribed time listed on TDS.
3. Apply the lighter of the two colors of ONYX HD to hiding.
4. Using an infrared temperature meter, measure this painted panel temperature. When the temperature is the same as an unpainted panel or bumper stand, it is ready to accept tape.
5. Apply K-UTG Gold tape along two tone edge. Using a tack cloth, apply light pressure to seal the tape to the surface and mask as necessary.
6. Apply second ONYX HD color to hiding and flash.
7. Remove masking and slowly pull tape at a 90° angle from how it is applied.
8. Apply your choice of VOC compliant R-M clearcoat according to the technical directions.

**Note:** This process does not require the use of BCH10 basecoat hardener. BCH10 will slow drying process and risk potential tape tracking.